

HEAT TREATED ASH DECKING

*all drawings are for reference only, and are not exactly to scale.

Muskoka Lumber’s quality heat treated ash decking has undergone a thermal modification process, which cooks out any larvae, parasites, and sugars – making it more resistant to insects, fungi, and mold. Heat treated decking lasts longer (without chemical treatment), and in addition to being less likely to rot, it is beautiful. (*for sizing availability, see table below)

HEAT TREATED ASH DECKING PROFILES AVAILABLE IN:



GROOVED

*hidden fasteners (mantis clips)



NON-GROOVED



Thermally modified ash weathers beautifully, as the elements naturally lighten its grain to produce a soft gray hue over time.



HEAT TREATED ASH DECKING PROFILE:

FINISHED DIMENSIONS:

GROOVED	1" x 5-1/8"	1" x 5-3/4"
NON-GROOVED	1" x 5-1/8"	1" x 5-3/4"
TRIM BOARD	1" x 7-1/4"	1" x 9-1/4"

*end matching comes standard on all decking profiles (grooved and non-grooved)



- **KNOT FREE**
(resulting in an even look and feel)
- **SMOOTH FINISH**
(enjoy a splinter-free, comfortable surface)
- **CHEMICAL-FREE MODIFICATION**
(all-natural process for high class durability)
- **SUSTAINABLY SOURCED**
(wood sourced from sustainable forests)

